



PRODUCT SPECIFICATION

PVC Offtake TO011715R and PO0117

Supplier catalogue reference

UNCONTROLLED COPY

DOCUMENT REF.

PVC OFFTAKE

SUBJECT

Catalogue reference

VERSION

1

DOCUMENT DATE

05/10/2026

PRODUCT OVERVIEW

PRODUCT	PVC Offtake
SUPPLIER	Waverley Plastics, Zimbabwe
APPLICATION	Drip tape to PVC-U supply pipe

16 mm

NOMINAL TAPE SIZE

FITTING REFERENCE SPECIFICATIONS

TO011715R VARIANT	De17 x 15 mm; grommet RR011613
PO0117 VARIANT	Dn17; grommet RR011608 (older catalogue)
PUNCH HOLE, BOTH VARIANTS	16 mm hole diameter
CONNECTIONS	Tape-lock outlet to PVC-U grommet
BODY MATERIAL	Polypropylene (PP), family specification
TAPE WALL THICKNESS	Up to 0.5 mm, Waverley nut-joint range

Nominal 16 mm tape range. De17/Dn17 are supplier designations. Use each model's specified grommet.

SUPPLIED CONFIGURATION

TO011715R and PO0117 are separate stocked variants. Match each model to its specified grommet. Do not interchange RR011613 and RR011608 without compatibility confirmation.

INSTALLATION CHECK

Confirm tape fit and the assembled-system pressure limit before use.

Maximum Pressure Rating 3 BAR

SOURCE AND REVISION

official model table - undated; checked 05 October 2026
Waverley Plastics drip-fitting family specifications - dated; checked 05
October 2026 manufacturer catalogue, PDF page 23 (PO0117)

DISCLAIMER

Supplier reference only. Model selection is supported by Waverley Plastics records; this sheet does not certify the delivered unit or its pressure rating. Confirm suitability before installation.